

# Weechat - with Bouncer

## Join a server

```
/server add BNC my.bouncer.net/6697 -ssl -username=username/network -password=password -autoconnect  
/save  
/connect <servername>
```

## Get ZNC sha

```
cat ~/.znc/znc.pem | openssl x509 -sha512 -fingerprint -noout | tr -d ':' | tr 'A-Z' 'a-z' | cut -d = -f 2
```

## enter fingerprint

```
/set irc.server.BNC.ssl_fingerprint MD5_or_SHA256_or_SHA512_fingerprint_here
```

## Join Freenode

```
/server add freenode chat.freenode.net/6697 -ssl -autoconnect
```

## accept self signed ssl certificate

```
/set irc.server.example.ssl_verify off
```

## Set autojoin Channels

```
/set irc.server.<servername>.autojoin "#<channel1>,#<channel2>,#..."
```

# Hide Username from Weechat window

you may want to show off your weechat with a screenshot and may want to hide your Username by default, to do this, enter the following in weechat:

```
/script install iset.pl  
/iset input  
/set weechat.bar.input.items "[input_search],[input_paste],input_text"
```

## set and register Nickname

### sasl

```
/set irc.server.<ircserver>.sasl_mechanism PLAIN  
/set irc.server.<ircserver>.sasl_username <login>  
/set irc.server.<ircserver>.sasl_password <password>  
/save  
/reconnect <ircserver>
```

## Nickserv

```
/nick <yournickname>  
/msg nickserv register <password> <email>
```

After that, you should get an email with your verification code. Verify via:

```
/msg nickserv identify <verification-code>
```

# Set Username for specific Server

```
/set irc.server.<server>.nicks <yournickname>
```

# Set Char length in front of messages

```
/set weechat.look.prefix_align_max <integer>
```

---

Revision #5

Created 19 November 2021 01:57:19 by tinfoil-hat

Updated 22 January 2025 06:37:25 by tinfoil-hat